







HiLook-IP

Items	Description	User Price
IPC-B120	 1/2.8" progressive scan CMOS-1920 × 1080@30fps -2.8 mm fixed lens- H.264+, H.264- Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR	ناموجود
IPC-B120-D/W	 2 MP Outdoor Fixed Bullet Network Camera with Build-in Mic High quality imaging with 2 MP resolution Efficient H.264 compression technology to save bandwidth and storage Clear imaging against strong back light due to DWDR technology Built-in microphone for real-time audio security Wireless connection for convenient installation and use	ناموجود
IPC-B120H	 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR, -2.8/4/6mm fixed lens BLC, DC12V & PoE,-up to 30m IR- Support mobile monitoring via Hik-Connec *power supply no included-DWDR-Front Cover: Metal-Back Cover & Bracket: Plastic-IP67	IRR 23,520,000
IPC-B121H	 1/2.8" progressive scan CMOS 3D DNR 1920 × 1080@30fps Up to 30 m IR range 2.8 mm/4 mm fixed lens IP67, DWDR, H265	IRR 19,760,000
IPC-B121H-M	 2 MP Fixed Bullet Network Camera High quality imaging with 2 MP resolution Efficient H.265+ compression technology Clear imaging against strong back light due to DWDR technology, (IP67) EXIR 2.0: advanced infrared technology with long IR range	ناموجود
IPC-B140H	 4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, DWDR- DC12V & PoE,2.8/4/6mm fixed lens, Support mobile monitoring via Hik-up to 30m IR, Connec *power supply no included-Front Cover: Metal Back Cover & Bracket: Plastic-IP67	IRR 25,290,000
IPC-B140H-M	 4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, DWDR- DC12V & PoE,2.8/4/6mm fixed lens, Support mobile monitoring via Hik-up to 30m IR, Connec *power supply no included-Front Cover: Metal Back Cover & Bracket: Plastic-IP67	ناموجود
IPC-B150H	 High quality imaging with 5 MP resolution Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) 3D DNR technology delivers clean and sharp images Easy installation with Power over Ethernet (PoE) technology	IRR 32,800,000
IPC-B220	 1/2.8" progressive scan CMOS - Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream-DWDR-3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application	IRR 20,280,000
IPC-B220-D	 1/2.8" progressive scan CMOS - Up to 2.0 megapixel high resolution-H264- 4 mm Lens-Up to 30 m IR distance-Dual stream-DWDR-3D DNR (Digital Noise Reduction)-BLC-IP67- Mobile monitoring via mobile application- D model only support 12VDC power supply	IRR 19,370,000
IPC-T120	 2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), DWDR -H.264+&H.264-, 2.8/4/6mm fixed lens- BLC, - DC12V & PoE -,up to 10m IR- Support mobile monitoring via Hik-Connec *power supply no included-Eyeball-Plastic-Cover: Plastic-Indoor-ip67	IRR 19,760,000
IPC-T120-D	 1/2.8" progressive scan CMOS-Up to 2.0 megapixel -2.8 mm fixed focal lens-H264+ - 10 m IR range-Dual stream-DWDR-3D DNR (Digital Noise Reduction)- Mobile monitoring via mobile application-IP 67- D model only support 12VDC power supply	IRR 18,970,000




IPC-T220-H		2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR,DWR, BLC, DC12V & PoE,-up to 30m IR-Support mobile monitoring via HikConnect *power supply no included-2.8/4/6mm fixed lens-Eyeball: MetalCover: Plastic-IP67	IRR 22,610,000
IPC-T221-H		2 MP Fixed Turret Network Camera High quality imaging with 2 MP resolution, Efficient H.265+ Clear imaging against ,strong back light by DWDR technology Water and dust resistant (IP67) (PoE) technology	IRR 20,800,000
IPC-T220		1/2.8" progressive scan CMOS BLC/3D DNR, 1920 x 1080@30fps, IP67 2.8, 4, 6 mm fixed lens, Digital WDR, H.264+, H.264 Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON);	IRR 22,350,000
IPC-T240H		4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, up to 30m IR- 3D DNR-DWDR, BLC, DC12V & PoE-2.8/4/6mm fixed lens,-Support mobile monitoring via Hik-Connect *power supply no included-Eyeball: Metal-Cover: Plastic- IP67	IRR 27,000,000
IPC-D120		1/2.8" progressive scan CMOS-2 MP-1920 x 1080@30fps-2.8mm fixed lens-H.264+, H.264-Color: 0.01 Lux @(F1.2, AGC ON), 0.028 Lux @(F2.0, AGC ON)-BLC/3D DNR-IP67-Digital WDR- IK 10	IRR 22,920,000
IPC-D120H		2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264, 3D DNR,-2.8/4/6mm fixed lens- BLC, DC12V & PoE,DWDR- Support mobile monitoring via Hik-Connect *power supply no included-up to 30m IR-Base: Metal-Cover: Plastic-IP67, IK10	ناموجود
IPC-D121H		2 MP Fixed Dome Network Camera Efficient H.265+ compression technology Clear imaging against strong back light due to DWDR technology Water and dust resistant (IP67) and vandal proof (IK10) Easy installation with power over Ethernet (PoE) technology	IRR 19,760,000
IPC-D121H-M		2 MP Fixed Dome Network Camera Efficient H.265+ compression technology Clear imaging against strong back light due to DWDR technology Water and dust resistant (IP67) and vandal proof (IK10) Easy installation with power over Ethernet (PoE) technology-METAL CASE	IRR 18,290,000
IPC-D140H		4.0 MP IR NetworkDome Camera,1/3" progressive scan CMOS, 3D DNR (Digital Noise Reduction), 2560 x 1440@20fps Up to 30 m IR range, 2.8 mm/4 mm/6 mm fixed lens,PoE (Power over Ethernet),H.265+, H.265, H.264+, H.264 IP67, IK10, Dual stream, 120 dB WDR.	IRR 29,170,000
IPC-D150H		High quality imaging with 5 MP resolution Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Water and dust resistant (IP67) and vandal resistant (IK10) 3D DNR technology delivers clean and sharp images Easy installation with Power over Ethernet (PoE) technology	IRR 35,290,000
Vari-Focal Series			
IPC-B620H-V		2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR ,DWDR- BLC, DC12V & PoE, TF card slot, up to 30m IR-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 41,260,000
IPC-B620H-Z		2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N),H.265+/H265/H.264+&H.264, 3D DNR, BLC, -up to 30m IR-DC12V & PoE, -DWDR- TF card slot,-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 46,240,000
IPC-B621-V		2 MP Varifocal Bullet Network Camera Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to DWDR technology(IP66) -V: model with manual vari-focal lens Built-in microphone enhances safety with video/audio in tandem	IRR 39,910,000
IPC-B621-Z		2 MP Varifocal Bullet Network Camera High quality imaging with 2 MP resolution, Efficient H.265+ Clear imaging against strong back light due to DWDR technology(IP66) -Z: model with motorized vari-focal lens Built-in microphone enhances safety with video/audio in tandem	IRR 45,450,000
IPC-B640H-V		4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot, WDR-Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 39,800,000
IPC-B640H-Z		4MP- 1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264, 3D DNR, BLC, up to 30m IR- DC12V & PoE, TF card slot,-WDR- Support mobile monitoring via Hik-Connect *power supply no included-2.8~12mm motorized vari-focal lens-Body&Bracket: Metal-SunShield: Plastic-IP67	IRR 51,370,000

IPC-T620-Z		2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.264+&H.264, 3D DNR, BLC,-WDR- up to 30m IR-DC12V & PoE,Support mobile monitoring via Hik-Connect *power supply no included 2.8~12mm VF lens-Eyeball: MetalCover: Plastic-IP67	IRR 46,630,000
IPC-D620H-V		2MP-1/2.8" Progressive CMOS, ICR, 1920x1080:25fps(P)/30fps(N), H.265+/H265/H.264+&H.264,DWDR- 3D DNR, BLC,2.8~12mm varifocal lens - DC12V & PoE, TF card slot,-up to 30m IR-- Support mobile monitoring via Hik-Connect *power supply no included -Full Metal-IP67, IK10	IRR 41,260,000
IPC-D620H-Z		1/2.8" progressive scan CMOS-2 MP-1920 x 1080@30fps- 2.8 mm to 12 mm manual/motorized (with -Z) vari-focal lens- H.265+, H.265, H.264+, H.264-Dual stream- DWDR -3D DNR (Digital Noise Reduction)-Up to 30 m IR range-PoE (Power over Ethernet)- IP67, IK10	IRR 50,580,000
IPC-D640H-V		4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264,WDR, 3D DNR, BLC,up to 30m IR- DC12V & PoE, TF card slot--2.8~12mm vari-focal lens- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10	IRR 44,810,000
IPC-D640H-Z		4MP-1/3" Progressive CMOS, ICR, 2560x1440:20fps(P)/(N), H.265+/H265/H.264+&H.264,WDR, 3D DNR, BLC,up to 30m IR- DC12V & PoE, TF card slot--2.8~12mm vari-focal lens- Support mobile monitoring via Hik-Connect *power supply no included - Full Metal-IP67, IK10	ناموجود




PanoVu Mini Series IR Network PTZ Camera















PTZ-P332ZI-DE3		System Functions 1 3-ch panoramic images in different directions and 1-ch close-up image 1 PTZ linkagel Up to 10 m IR radius Panoramic Cameral Three 1/2.8" progressive scan CMOS1 3-ch 1920 x 1080@30fps resolution! Horizontal FOV: 128.5° x 3 PTZ Cameral 1/2.8" progressive scan CMOS1 Up to 1920 x 1080@30fps resolution! 4x optical zoom, 8x digital zoom	ناموجود
----------------	-----------------------------------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------

IP PTZ Camera

PTZ-N4215-DE3		1/2.8" progressive scan CMOS Up to 1920 x 1080 resolutionMin. illuminat Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR 15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC 12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compression Up to 24 programmable privacy masks Support ROI	ناموجود
PTZ-N4215I-DE		1/2.8" progressive scan CMOSUp to 1920 x 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IR Up to 100 m IR distance15x optical zoom, 16x digital zoom 120dB WDR, 3D DNR, HLC, BLC, Smart IR12 VDC & PoE+ (802.3at, class4) Support H.265+/H.265 video compressionUp to 24 programmable privacy masks Support ROI	IRR 79,500,000
PTZ-N4225I-DE		1/2.8" progressive scan CMOSUp to 1920 x 1080 resolution Min. illumination: Color: 0.005 Lux @(F1.6, AGC ON) B/W: 0.001 Lux @(F1.6, AGC ON) 0 Lux with IRUp to 100 m IR distance 25x optical zoom, 16x digital zoom120dB WDR, 3D DNR, HLC, BLC, Smart IR 12 VDC & PoE+ (802.3at, class4)Support H.265+/H.265 video compression Up to 24 programmable privacy masksSupport ROI	IRR 99,400,000
PTZ-N2404I-DE3		Two-inch 4 MP camera with pan, tilt and zoom (4x) ability Efficient H.265+ compression technology to save bandwidth and storage Clear imaging against strong back light due to 120 dB true WDR technology Great night-time performance with up to 20 m enhanced IR Water and dust resistant (IP66), and vandal proof (IK10)	ناموجود

Network Video Recorder

NVR-104-B		Full channel recording at up to 4 MP resolution-40Mbps Bit Rate Input Max (up to 4-ch IP video),Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability- 2-ch@ 4MP-4-ch@1080p	IRR 16,360,000
NVR-108-B		Full channel recording at up to 4 MP resolution-60Mbps Bit Rate Input -Max (up to 8-ch IP video),Output Bandwidth 40Mbps- H.264, 1 SATA interface 6TB, mini 1U case(Plastic)-HDMI Output 1, up to 1080P-Decoding Capability-2-ch@4 MP, 4-ch@1080p	IRR 19,920,000
NVR-108-B/8p		4-ch Mini 1U 4 PoE 4K NVR,Up to 8 channel IP cameras can be connected Plug & Play with 8 Power-over-Ethernet (PoE) interfaces Supports decoding H.264+/H.264 multiple video formats Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording	IRR 30,490,000

NVR-104H-D		4-ch Mini 1U 4 PoE NVR H.265+/H.265/H.264+/H.264 video compression Up to 40 Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth Up to 4-ch network camera inputs, Up to 4-ch 1080p decoding capability HDMI and VGA simultaneous output	IRR 15,530,000
NVR-108H-D		4-ch Mini 1U NVR H.265+/H.265/H.264+/H.264 video compression Up to 60 Mbps incoming bandwidth, and 60 Mbps outgoing bandwidth Up to 8-ch network camera inputs, Up to 4-ch 1080p decoding capability HDMI and VGA simultaneous output	IRR 21,750,000
NVR-104MH-C		Recording at up to 8 MP resolution-40Mbps Bit Rate Input- Max (up to 4-ch IP video UP to 8MP), Output Bandwidth 80Mbps- H.265-, 1 SATA (6TB) interface, standalone 1U 315 case(Metal)- HDMI Output 1CH 4K, --Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p	IRR 26,770,000
NVR-104MH-D		Up to 4 channel IP cameras can be connected Supports decoding H.265+/H.265/H.264+/H.264 multiple video formats Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording.	IRR 19,210,000
NVR-104MH-D/4P		Up to 4 channel IP cameras can be connected Plug & Play with 4 Power-over-Ethernet (PoE) interfaces Supports decoding H.265+/H.265/H.264+/H.264 multiple video formats Up to 4-ch @ 1080p decoding capacity 1 HDD for continuous video recording	IRR 30,670,000
NVR-104MH-C/4P		Recording at up to 8 MP resolution-40Mbps Bit Rate Input- Max (up to 4-ch IP video UP to 8 MP) , Output Bandwidth 80Mbps- H.265-, 1 SATA (6TB) interface, 4 independent PoE network interfaces, 1U 315 case(Metal)-HDMI Output 1ch 4k-Decoding Capability 1-ch @ 8 MP 4-ch @ 1080P	ناموجود
NVR-108MH-C		Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8 MP), Output Bandwidth 80Mbps- H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)- HDMI Output 1CH 4K, Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p	IRR 35,730,000
NVR-108MH-D		IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing, bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF, H.265+/H.265/ H.264+/H.264, 1 SATA interface, Capacity Up to 6TB capacity for each disk,	IRR 24,500,000
NVR-208MH-C		Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8 MP), Output Bandwidth 80Mbps- H.265, 2 SATA interface(6TB), standalone 1U 315 case(Metal)- HDMI Output 1CH 4K, Decoding Capability: -1-ch @ 8 MP / 4-ch @ 1080p	IRR 42,170,000
NVR-108MH-C/8P		Recording at up to 8 MP resolution-80Mbps Bit Rate Input- Max (up to 8-ch IP video UP to 8mp), Output Bandwidth 80Mbps- H.265, 1 SATA interface(6 TB), 8 independent PoE network interfaces, standalone 1U 315 case(Metal)-HDMI Output 1ch 4k, - Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	ناموجود
NVR-108MH-D/8P		IP video input 8ch, Incoming bandwidth 60 Mbps Outgoing, bandwidth 60 Mbps, Recording resolution 4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF, H.265+/H.265/ H.264+/H.264, 1 SATA interface, Capacity Up to 6TB capacity for each disk,	IRR 47,500,000
NVR-116MH-C		Recording at up to 8 MP resolution-160Mbps Bit Rate Input- Max (up to 16-ch IP video UP to 8MP), Output Bandwidth 80Mbps- H.265, 1 SATA interface(6TB), standalone 1U 315 case(Metal)-HDMI Output 1CH 4K, Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	IRR 37,150,000
NVR-216MH-C		Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video), Output Bandwidth 80Mbps, - H.265-2, SATA up to 6TB per HDD interface, standalone 1U 385 case(Metal)-HDMI Output 1 ch 4k -Decoding Capability: 1-ch @ 8 MP / 4-ch @ 1080p	ناموجود
NVR-216MH-C/16P		Recording at up to 8 MP resolution-160Mbps Bit Rate Input Max (up to 16-ch IP video) Output Bandwidth 80Mbps, H.265, 2 SATA (up to 6TB per HDD) interface, 16 independent PoE network interfaces, standalone 1U 385 case(Metal)-HDMI Output 1 ch 4k, -Decoding Capability 1-ch @ 8 MP / 4-ch @ 1080p	ناموجود