



RADIS
مركز كاشف الاحتيال

Tiandy















PRICE LIST








☎ 011177700111

WWW.RADIS-CO.COM

📷 RADIS.NET

Network Camera - NVR

SKU(M)	Items	Description	گارانتی مادیران User Price
supe rlight series			
230510	TC-C32GN Spec: I5/E/Y/C/2.8mm	 2MP Fixed IR Bullet Camera 1920x1080@30fps, Metal+Plastic, 1/2.8", 0.02Lux, Digital WDR, 50m IR FOV: 99.7°, S+265/H.265/H.264, IP67 Mic-in, No Power Cable, No Reset Bottun, No SD-Card	IRR 15,220,000
230750	TC-C34GN Spec: I5/E/Y/C/2.8mm	 2560x1440@25fps, Metal+Plastic, 1/2.7", 0.02Lux, Digital WDR, 50m IR FOV: 103.4°, S+265/H.265/H.264, IP67, Mic-in, No Power Cable, No Reset Bottun, No SD-Card	IRR 20,290,000
230743	TC-C32GS Spec: I5/E/Y/C/SD/2.8mm	 1920x1080@30fps, Metal+Plastic 1/2.8", 0.02Lux, WDR 120dB, 50m IR FOV: 99.7°, S+265/H.265/H.264, IP67 Mic-in, No Power Cable, No Reset Bottun, 512GB SD-Card	IRR 18,700,000
	TC-C34GS Spec: I5/E/Y/C/SD/2.8mm	 4MP Fixed Starlight IR Bullet Camera 2560x1440@25fps, Metal+Plastic 1/2.7", 0.002Lux, Digital WDR, 50m IR, FOV: 103.4°, S+265/H.265/H.264, IP67 Mic-in, No Power Cable, No Reset Bottun, 512GB SD-Card	IRR 25,340,000
230534	TC-C34GS Spec: I5/E/Y/C/4mm/V4.0	 1/2.7" CMOS, F1.6, Fixed Iris, 120dB, 50m IR, 0.002Lux, 2560x1440@30fps, Built-in Mic, IP67, PoE, Metal+Plastic housing	IRR 25,340,000
230511	TC-C32HN Spec: I3/E/Y/C/2.8mm/V4.0	 1/2.8" CMOS, F2.0, Fixed Iris, Digital WDR, 30m IR, 0.02Lux, 1920x1080@30fps, Built-in Mic, IP67, PoE, Metal+Plastic housing, No Power Cable	IRR 15,220,000
230741	TC-C32HN Spec: I3/E/Y/C/2.8mm/V4.0	 1/2.8" CMOS, F2.0, Fixed Iris, Digital WDR, 30m IR, 0.02Lux, 1920x1080@30fps, Built-in Mic, IP67, PoE, Metal+Plastic housing	IRR 16,140,000
230744	TC-C32HS Spec:I3/E/Y/C/SD/2.8mm	 2MP Fixed Starlight IR Turret Camera 1920x1080@30fps, Metal+Plastic 1/2.8", 0.002Lux, WDR 120dB, 30m IR FOV: 99.7°, S+265/H.265/H.264, IP66 Mic-in, No Power Cable, No Reset Bottun, 512GB SD-Card	IRR 18,700,000
	TC-C34HS Spec: I3/E/Y/C/SD/2.8mm/V4.0	 4MP Fixed Starlight IR Turret Camera 2560x1440@25fps, Metal+Plastic, 1/2.7", 0.002Lux, Digital WDR , 30m IR FOV: 99.7°, S+265/H.265/H.264, IP66 Mic-in, No Power Cable, No Reset Bottun , 512GB SD-Card	IRR 25,340,000
230512	TC-C34HS Spec: I3/E/Y/C/2.8mm/V4.0	 2560x1440@25fps, Metal+Plastic 1/2.7", 0.002Lux, WDR 120dB, 30m IR FOV:103.4°, S+265/H.265/H.264, IP66 Mic-in, No Reset Button, No SD-Card	IRR 25,340,000
230746	TC-C34HN Spec: I3/E/Y/C/2.8mm	 4MP Fixed IR Turret Camera 2560x1440@25fps, Metal+Plastic 1/2.7", 0.02Lux, Digital WDR, 30m IR FOV: 99.7°, S+265/H.265/H.264, IP66 Mic-in, No Power Cable, No Reset Bottun, No SD-Card	IRR 20,290,000
lite series			
	TC-C32WP Spec:I5/E/M/Y/4mm	 1/2.8" CMOS, F1.6, Fixed Iris, Digital WDR, 50m IR, 0.0008Lux, 1920x1080@30fps, 512 GB SD card slot, Built-in Mic, Reset Button, IP67, PoE Metal model: cost added 4USD	IRR 35,860,000
230524	TC-C32WP Spec: W/E/Y/4mm	 1/2.8" CMOS, F1.6, Fixed Iris, Digital WDR 2 Warm lights, 15~20m, 0.0008Lux, 1920x1080@30fps, 512 GB SD card slot, Built-in Mic, Reset Button, IP67, PoE Metal model: cost added 4USD	IRR 27,732,000
	TC-C32WP Spec: W/E/Y/2.8mm	 2.8/1" CMOS, F1.6, Fixed Iris, Digital WDR 2 Warm lights, 20~15m, 0.0008Lux, 1920x30@1080fps, 512 GB SD card slot, Built-in Mic, Reset Button, IP67, PoE	IRR 27,730,000

230522	TC-C32XP Spec:W/E/Y/2.8mm		1/2.8" CMOS, F1.6, Fixed Iris, Digital WDR, 2 Warm lights, 15~20m, 0.0008Lux, 1920x1080@30fps, 512 GB SD card slot, Built-in Mic, Reset Button, IP67, PoE Metal model: cost added 4USD	IRR 31,460,000
230523	TC-C34XP Spec:W/E/Y/M/2.8mm/V4.0		1/2.8" CMOS, F1.6, Fixed Iris, Digital WDR, 0.0008Lux, 1920x1080@30fps, 512 GB SD card slot, Built-in Mic, Reset Button, IP67, PoE Metal model: cost added 4USD	IRR 39,340,000
	TC-C33XN Spec: I3/E/Y/2.8mm		1/2.7" CMOS, F2.0, Fixed Iris, Digital WDR, 30m IR, 0.02Lux, 2304x1296@20fps, 512 GB SD card slot, Built-in Mic, Reset Button, IP67, PoE, Metal+Plastic housing	IRR 24,860,000
230516	TC-C34WS Spec:I5/E/Y/M/2.8mm		1/2.8" CMOS, F1.6, Fixed Iris, 120dB, 50m IR, 0.002Lux, 2560x1440@25fps, 512 GB SD card slot, Built-in Mic, Reset Button, IP67, PoE Metal model: cost added 4USD	IRR 44,302,000
	TC-C34WS Spec:I5/E/Y/M/4mm		1/2.8" CMOS, F1.6, Fixed Iris, 120dB, 50m IR, 0.002Lux, 2560x1440@25fps, 512 GB SD card slot, Built-in Mic, Reset Button, IP67, PoE Metal model: cost added 4USD	IRR 34,694,000
230535	TC-C34WP Spec:W/E/Y/M/4mm/V4.0		1/2.8" CMOS, F1.6, Fixed Iris, 120dB, 2 Warm lights, S+265/H.265/H.264, 15~20Mm IR, 0.0008Lux, 2560x1440@25fps, IP67, PoE, Metal+Plastic housing	IRR 42,080,000
230518	TC-C34KS Spec:I3/E/Y/2.8mm		1/2.8" CMOS, F1.6, Fixed Iris, 120dB, 30m IR, 0.002Lux, 2560x1440@25fps, 512 GB SD card slot, Built-in Mic, Reset Button, IP67, IK10, PoE, Metal+Plastic housing	IRR 36,346,000
	TC-C33WN Spec:I5/E/Y/4mm		1/2.9" CMOS, F2.0, Fixed Iris, Digital WDR, 50m IR, 0.02Lux, 1920x1080@30fps, 512 GB SD card slot, Built-in Mic, Reset Button, IP67, PoE Metal model: cost added 4USD	IRR 22,600,000
230521	TC-C35US Spec:I8/A/E/Y/M/2.8-12mm		1/2.8" CMOS, F1.6-F3.3, Fixed Iris, 120dB, 80m IR, 0.002Lux, 2592x1944@20fps, 512 GB SD card slot, Built-in Mic, Reset Button, IP67, PoE, full metal housing	IRR 59,290,000
	TC-C38WS Spec:I5/E/Y/M/4mm		1/2.8" CMOS, F1.6, Fixed Iris, 120dB, 50m IR, 0.01Lux, 3840x2160@20fps, 512 GB SD card slot, Built-in Mic, Reset Button, IP67, PoE, full metal housing	IRR 58,334,000
230520	TC-C38KS Spec:I3/E/Y/2.8mm		1/2.8" CMOS, F1.6, Fixed Iris, 120dB, 30m IR, 0.01Lux, 3840x2160@20fps, 512 GB SD card slot, Built-in Mic, Reset Button, IP67, IK10, PoE, Metal+Plastic housing	IRR 69,360,000
	TC-H323Q Spec:04X/I/E		<ul style="list-style-type: none"> -Early Warning (EW) -Up to 1920x1080@30fps -Min. illumination Color: 0.002Lux@F1.4 -Optical zoom: 4x, digital zoom 16x -Smart IR, IR Range: 30m -Support Human/Vehicle Classification -Built-in Mic&Speaker -S+265/H.265/H.264/M-JPEG 	IRR 124,300,000
230678	TC-H324S Spec: 25X/I/E		PoE+, 1/2.8" Starlight sensor, 1080P@30fps, 150m IR, 25x optical zoom, Speed 0.1°~200°/s, Heater, TVS 6000V protection, Low illumination: 0.002Lux	IRR 218,970,000
	TC-H356S Spec:30X/I/E++/A		<ul style="list-style-type: none"> -Optical zoom: 30x, digital zoom 16x -Smart IR, IR Range: 200m -S+265/H.265/H.264/M-JPEG -Intelligent monitoring: Face Capture mode -Support Human/Vehicle Classification -Support Auto-tracking -Plugin Free -IP67 	IRR 480,954,000
200762	TC-A3563 Spec:44X/I/A		<ul style="list-style-type: none"> - Auto-Tracking Early Warning (AEW) - Up to 3072x1728@20fps - Min. illumination Color: 0.0008Lux@F1.5 - Optical zoom: 44x, digital zoom 16x - Built-in Speaker - Support Human/Vehicle Classification - Support Laser Point - Face Capture/Intelligent monitoring mode - Smart IR, IR Range: 180m - S+265/H.265/H.264/M-JPEG - IP66 	IRR 1,020,217,000

230528	TC-R3105 Spec: I/B		5-ch, 50Mbps/40Mbps, recording resolution up to 6MP, decoding ability 1*6MP, 3*1080p, 4*720p, video output: 1 HDMI & 1VGA simultaneous output, USB interface: 2xUSB 2.0	IRR 32,231,000
230533	TC-R3105 Spec: I/B/L		5CH 1HDD 1U NVR, 5 IP camera input + 2 CH expansion = 7CH S+265/H.265/H.264 video formats Max 50/40 Mbps incoming/Outgoing bandwidth. Up to 6M Resolution Recording Synchronous Decode: 1x8MP, 3x1080P, VCA detection alarm is supported HDMI and VGA simultaneous output, HDMI Video output at up to 1080P (1920 x 1080) 1 SATA interface, up to 10TB for 1 HDD 1CH Audio output, 2 USB Ports 1*10/100 Mbps Network Card, P2P support	IRR 21,580,000
200529	TC-R3110 Spec: I/B		10-ch, 50Mbps/40Mbps, recording resolution up to 6MP, decoding ability 1*6MP, 3*1080p, 4*720p, video output: 1 HDMI & 1VGA simultaneous output, USB interface: 2xUSB 2.0	IRR 35,570,000
230530	TC-R3120 Spec: I/B		20-ch, 80Mbps/80Mbps, recording resolution up to 8MP, decoding ability 1*8MP, 4*1080p, 8*720p, video output: 1 HDMI & 1VGA simultaneous output, USB interface: 2xUSB 2.0, N+M	IRR 39,130,000
	TC-R3120 Spec: I/B/V3.0		S265+H.265/H.264 video formats DMI and VGA simultaneous output HDMI Video output at up to 4K (1 2160x3840 SATA interface, up to 10TB for 1 HDD 1xRJ45 self-adaptive 100/10 Mbps network interface CA detection alarm is supported	IRR 55,935,000
230531	TC-R3220 Spec: I/B/K		20-ch, 120Mbps/100Mbps, recording resolution up to 8MP, decoding ability 1*8MP, 4*1080p, 8*720p, video output: 1 HDMI & 1VGA simultaneous output, alarm I/O 4/1, USB interface: 2xUSB 2.0, ANR, N+M	IRR 85,770,000
230681	TC-R3220 Spec: I/B/K/V3.0		20-ch, 120Mbps/100Mbps, recording resolution up to 8MP, decoding ability 1*8MP, 4*1080p, 8*720p, video output: 1 HDMI & 1VGA simultaneous output, alarm I/O 4/1, USB interface: 2xUSB 2.0, ANR, N+M	IRR 85,770,000
230749	TC-R3220 Spec: I/B/P16/K/V3.0		HD Input: Plug and play S+265/H.265/H.264 video formats • Connectable to the third-party network cameras • Up to 20-channel input • 16 PoE ports • Supports live view, storage, and playback of the connected camera at up to 8MP resolution HD Output • 1xHDMI and 1xVGA simultaneous outputs • HDMI Video output at up to 4K (3840 x 2160) resolution HD Storage • 2 SATA interfaces, up to 10TB for each HDD • S+265 compression effectively reduces the storage space and costs by up to 75% HD Transmission • 1xRJ45 self-adaptive 10/100/1000 Mbps network interface • PoE Port: 16xRJ45 self-adaptive 10/100 Mbps network interfaces Various Applications • Centralized management of IP cameras, including configuration, information import/export, real-time information display, upgrade, etc. • Connectable to smart IP cameras from Tiandy and the recording, playing back, and backing up of VCA	IRR 163,850,000
230532	TC-R3240 Spec: I/B/N/H		40-ch, 320Mbps/320Mbps, recording resolution up to 12MP, decoding ability 4*8MP, 16*1080p, 32*720p, video output: 1 HDMI & 1VGA simultaneous output, alarm I/O 16/4, USB interface: 1xUSB 3.0 1xUSB 2.0, ANR, N+M	IRR 151,400,000
230575	TC-R3440 Spec: I/B/N/H/C		HD Input: S+265/H.265/H.264 video formats • Connectable to the third-party network cameras • Up to 40-channel input • Supports live view, storage, and playback of the connected camera at up to 12MP resolution HD Output • HDMI and VGA simultaneous output • HDMI Video output at up to 4K (3840x2160) resolution HD Storage • 4 SATA interfaces, up to 10TB for each HDD • S+265 compression effectively reduces the storage space and costs by up to 75% HD Transmission • 2xRJ45 self-adaptive 10/100/1000 Mbps network interfaces, Various Applications • Centralized management of IP cameras, including configuration, information import/export, real-time information display, upgrade, etc. • Connectable to smart IP cameras from Tiandy and the recording, playing back, and backing up of VCA	IRR 167,810,000
	TC-R3440 Spec: I/B/P16/H		HD Input, • Plug and play S+265/H.265/H.264 video formats • Connectable to the third-party network cameras • Up to 40-channel input, 16 PoE ports • Supports live view, storage, and playback of the connected camera at up to 12MP resolution, HD Output • 1xHDMI and 1xVGA simultaneous outputs • HDMI Video output at up to 4K (3840 x 2160) resolution, HD Storage • 4 SATA interfaces, up to 10TB for each HDD • S+265 compression effectively reduces the storage, space and costs by up to 75% HD Transmission, • 1xRJ45 self-adaptive 10/100/1000 Mbps network interface • PoE Port: 16xRJ45 self-adaptive 10/100 Mbps network interfaces, Various Applications • Centralized management of IP cameras, including	IRR 319,290,000
230710	TC-R3840 Spec: I/B/N		- S+265 Compression- Up to 12MP Resolution Recording - Support 40-ch Intelligent Analysis Process - Smart Search&Recording - Support ANR Function - Cloud upgrade, IPC Cloud upgrade - Plug in free - 2x HDMI, 2x VGA, Different Video Source, Max Resolution 4K - 8 SATA (Up to 10TB), Alarm I/O 16/4, Audio I/O 1/2, 3x USB - Dual Gigabit Network Interfaces - UI V3.0, Support free dragging of UI navigation bar - Support JBOD, RAID0, RAID1, RAID5, RAID6, RAID10 E39- CE, FCC	IRR 306,897,000
	TC-R31680 Spec: E/B/N		- S+265 Compression - Up to 12MP Resolution Recording - Support 80-ch Intelligent Analysis Process - Smart Search&Recording - Support ANR Function - Cloud upgrade, IPC Cloud upgrade- Plug in free - 2x HDMI, 2x VGA, Different Video Source, Max Resolution 4K - 16 SATA (Up to 10TB), Alarm I/O 16/4, Audio I/O 1/2, 3x USB - Dual Gigabit Network Interfaces - UI V3.0, Support free dragging of UI navigation bar - Support JBOD, RAID0, RAID1, RAID5, RAID6, RAID10 E40- CE, FCC	IRR 1,217,158,000

ultra series

	TC-A35555_0/A/2.8-12mm/9.54mm		<ul style="list-style-type: none"> - Dual TZ design - 5MP varifocal PTZ-bullet for overall scenario and 5MP speed dome for detailed view - Resolution up to 3072x1728@20fps - Min. illumination Color: 0.0008Lux@F1.0 (PTZ-bullet) - Optical zoom of PTZ-bullet: 4x, digital zoom 16x - Optical zoom of speed dome: 6x, digital zoom 16x; Smart IR, IR Range: 100m - Support blue&red flash warning; Built-in dual Mic& dual Speaker - Built-in Electronic Compass; Support video structure analysis - S+265/H.265/H.264/M-JPEG; Support Human/Vehicle Classification - Plugin Free- IP66 	IRR 1,228,668,000
pro series				
230525	TC-C32WS Spec:15/E/Y/M/4mm		1/2.8" CMOS, F1.6, Fixed Iris, 120dB, 50m IR, 0.001Lux, 1920x1080@30fps, 512 GB SD card slot, IP67, PoE, Built-in Mic, Reset button, Smart VCA function, Face capture mode, Full Metal Housing	IRR 47,551,000
	TC-C32MP Spec:15/A/E/Y/M/H/2.7-13.5mm/V4.0		<ul style="list-style-type: none"> - Full Metal Housing; Motorized Lens 2.7-13.5mm - Up to 1920x1080@30fps - S+265/H.265/H.264/M-JPEG - Min. illumination Color: 0.0004Lux@F1.2 - Smart IR, IR Range: 50m - Support Video Analytics - Support Human/Vehicle Classification - Support Face Capture Mode - Built-in Mic, audio I/O 1/1, alarm I/O 2/1 - Plugin Free - Operating Conditions -35°C-65°C, 0-95% RH - POE, IP67, IK10 	IRR 109,011,000
	TC-C32UP Spec:W/E/Y/M/H/4mm/V4.0		<ul style="list-style-type: none"> - Full Metal Housing - Up to 1920x1080@60fps; S+265/H.265/H.264/M-JPEG - Min. illumination Color: 0.0004Lux@F1.0 - 4 Warmlights, 20-30m - Support Video Analytics - Support Human/Vehicle Classification - Support Face Capture Mode - Built-in Mic, audio I/O 1/1, alarm I/O 2/1 - Plugin Free - Operating Conditions -40°C-65°C, 0-95% RH - POE, IP67 	IRR 76,979,000
	TC-C32TP Spec:18/A/E/Y/M/H/2.7-13.5mm/V4.0		<ul style="list-style-type: none"> - Full Metal Housing; Motorized Lens 2.7-13.5mm - Up to 1920x1080@30fps - S+265/H.265/H.264/M-JPEG - Min. illumination Color: 0.0004Lux@F1.2 - Smart IR, IR Range: 50m - Support Video Analytics - Support Human/Vehicle Classification - Support Face Capture Mode - Built-in Mic, Audio I/O 1/1, alarm I/O 2/1 - Plugin Free - Operating Conditions -35°C-65°C, 0-95% RH - POE, IP67, IK10 	IRR 109,011,000
	TC-C32TS Spec:18/A/E/Y/M/H/2.7-13.5mm/V4.0		<ul style="list-style-type: none"> - Full Metal Housing; Motorized Lens 2.7-13.5mm - Up to 1920x1080@30fps; S+265/H.265/H.264/M-JPEG - Min. illumination Color: 0.001Lux@F1.6 - Smart IR, IR Range: 80m - Support Video Analytics - Support Face Capture Mode - Built-in Mic, Audio I/O 1/1, alarm I/O 2/1 - Plugin Free - Operating Conditions -35-65°, 0-95% RH - POE, IP67 	IRR 72,194,000
200527	TC-C35TS Spec:18/A/E/Y/M/H/2.7-13.5mm		1/2.8" CMOS, F1.6-F3.3, Fixed Iris, 120dB, 80m IR, 0.001Lux, 2592x1944@30fps, 2MP@60fps, 512 GB SD card slot, IP67, PoE, Audio 1/1, Alarm 2/1, Reset button, Smart VCA function, Face capture mode, Full Metal Housing	IRR 86,065,000
	TC-A38N5 Spec:0/A/10-47mm		<ul style="list-style-type: none"> - 1/1.8 inch CMOS sensor, Focus: 10-47mm - Up to 3840x2160@30fps, Min. illumination Color: 0.01Lux@F1.35 - S+265/H.265/H.264/M-JPEG - Face capture/intelligent monitoring mode - 6 warm lights, up to 45m, IP67 	IRR 536,404,000
	TC-C38TS Spec:18/A/E/Y/M/H/2.7-13.5mm		<ul style="list-style-type: none"> - Full Metal Housing; Motorized Lens 2.7-13.5mm - Up to 3840x2160@20fps - S+265/H.265/H.264/M-JPEG - Min. illumination Color: 0.003Lux@F1.6 - Smart IR, IR Range: 80m - Support Video Analytics - Support Human/Vehicle Classification - Support Face Capture Mode - Audio I/O 1/1, alarm I/O 2/1 - Plugin Free - Operating Conditions -35°C-65°C, 0-95% RH - POE, IP67 	IRR 189,321,000
	TC-C35MP Spec:15/A/E/Y/M/H/2.7-13.5mm/V4.0		<ul style="list-style-type: none"> - Full Metal Housing; Motorized Lens 2.7-13.5mm - Up to 2592x1944@30fps, 1920x1080@60fps - S+265/H.265/H.264/M-JPEG - Min. illumination Color: 0.001Lux@F1.3 - Smart IR, IR Range: 50m - Support Video Analytics - Support Human/Vehicle Classification - Support Face Capture Mode - Built-in Mic, audio I/O 1/1, alarm I/O 2/1 - Plugin Free - Operating Conditions -35°C-65°C, 0-95% RH - POE, IP67, IK10, 140dB 	IRR 127,347,000
	TC-C35MS Spec:15/A/E/Y/M/H/2.7-13.5mm		<ul style="list-style-type: none"> - Full Metal Housing; Motorized Lens 2.7-13.5mm - Up to 2592x1944@30fps, 1920x1080@60fps - S+265/H.265/H.264/M-JPEG - Min. illumination Color: 0.001Lux@F1.6 - Smart IR, IR Range: 50m - Support Video Analytics - Support Human/Vehicle Classification - Support Face Capture Mode - Built-in Mic, audio I/O 1/1, alarm I/O 2/1 - Plugin Free - Operating Conditions -35°C-65°C, 0-95% RH - POE, IP67, IK10 	IRR 93,225,000
230643	TC-C35MS Spec:13/A/E/Y/M/2.8-12mm		<ul style="list-style-type: none"> - Full Metal Housing; Motorized Lens 2.8-12mm - Up to 2592x1944@20fps - S+265/H.265/H.264 - Min. illumination Color: 0.002Lux@F1.6 - 120dB WDR - Smart IR, IR Range: 30m - Support tripwire and perimeter - Built-in Mic, SD Card Slot, Reset Button - Operating Conditions -40°C-60°C, 0-95% RH - POE, IP67, IK10 	IRR 59,290,000
	TC-C35KS Spec:13/E/Y/M/H/2.8mm/V4.0		<ul style="list-style-type: none"> - Full Metal Housing - Up to 2592x1944@30fps, 1920x1080@60fps; S+265/H.265/H.264/M-JPEG - Min. illumination Color: 0.002Lux@F1.6 - Smart IR, IR Range: 30m - Support Video Analytics - Support Human/Vehicle Classification - Support Face Capture Mode - Built-in Mic, audio I/O 1/1, alarm I/O 1/1 - Plugin Free - Operating Conditions -40°C-65°C, 0-95% RH - POE, IP67, IK10 	IRR 53,374,420
	TC-C38MS Spec:15/A/E/Y/M/H/2.7-13.5mm		<ul style="list-style-type: none"> - Full Metal Housing; Motorized Lens 2.7-13.5mm - Up to 3840x2160@20fps - S+265/H.265/H.264/M-JPEG - Min. illumination Color: 0.003Lux@F1.6 - Smart IR, IR Range: 50m - Support Video Analytics - Support Human/Vehicle Classification - Support Face Capture Mode - Built-in Mic, audio I/O 1/1, alarm I/O 2/1 - Plugin Free - Operating Conditions -35°C-65°C, 0-95% RH - POE, IP67, IK10 	IRR 189,321,000
	TC-C35JS Spec:15/E/M/N/4mm/V4.0		<ul style="list-style-type: none"> - Full Metal Housing - Up to 2592x1944@30fps, 1920x1080@60fps - S+265/H.265/H.264/M-JPEG - Min. illumination Color: 0.002Lux@F1.6 - Smart IR, IR Range: 50m - Support Video Analytics - Support Human/Vehicle Classification - Support Face Capture Mode - Plugin Free - Operating Conditions -40°C-65°C, 0-95% RH - POE, IP67 	IRR 52,592,000

230679	TC-C34LP Spec:I5/A/E/MH/2.7-13.5mm		<ul style="list-style-type: none"> - Full Metal Housing - Motorized Lens 2.7-13.5mm - Up to 2560x1440@30fps, 1920x1080@60fps - S+265/H.265/H.264/M-JPEG - Min. illumination Color: 0.0004Lux@F1.2 - Smart IR, IR Range: 80m - Support Video Analytics - Support Human/Vehicle Classification - Support Face Capture Mode - Support Early Warning - Built-in Mic&Speaker, audio I/O 1/1, alarm I/O 2/1 - Plugin Free - Operating Conditions -35°C~65°C, 0~95% RH - POE, IP67, IK10 	IRR 118,090,000
	TC-C38JS Spec:I5/E/MN/4mm		1/2.8" CMOS, F1.6, Fixed Iris, 120dB, 50m IR, 0.01Lux, 3840x2160@20fps, 512 GB SD card slot, IP67, PoE, Reset button, Smart VCA function, Face capture mode, Full Metal Housing	IRR 89,882,000
	TC-A32P6 Spec:E/4mm		<ul style="list-style-type: none"> - 4mm Fixed Lens- Up to 1920x1080@30fps - S+265/H.265/H.264 - Min. illumination Color: 0.002Lux@ (F1.6, ACG ON) - Support People Counting - AI deep learning detection algorithm provides highly precise recognition rates≥98% - Self-adaptive to height from 2.5m to 4m, ease of installation - Plugin Free- Operating Conditions -35°~65°, 0~95% RH - POE, IP66 	IRR 156,332,000
	TC-NC1261		<ul style="list-style-type: none"> - Up to 4000x3072@20fps - S+265/H.265/H.264/M-JPEG - Support Ceiling, Wall, Table Mounting - Support Hardware Decoding and Software Decoding - Support 360° Panoramic View, 180° Panoramic View, 4PTZ, Fisheye+3PTZ Mode - Support Human/Vehicle Classification - Built-in Mic&Speaker - Smart IR, IR Range: 20m - Operating Conditions -35°~65°, 0~95% RH, POE, IP66, IK10 	IRR 348,040,000
	TC-H326S Spec:33X/I/E++/A		PoE++, 1/2.8" CMOS Sensor, 1080P@60fps, Auto-tracking, 200m IR, Speed 0.1°~180°/s, MicroSD card(256GB), IP67 waterproof, Low Illumination: 0.001Lux, Audio I/O 1/1, Alarm I/O 8/2, RS-485, BNC, Face capture mode, Human/Vehicle classification, Onvif Profile S/T	IRR 392,987,000